






















Product data
Floorify® Rigid Vinyl Planks & Tiles
 click

version: 1/05/2023

EN

Parameter	Norm	Performance		
Dimensions and basic data				
		Small tiles	Planks	
Width	ISO24337	305	178	mm
Length	ISO24337	610	1219	mm
Number of panels per pack	-	12	12	pc
m ² per pack	-	2,23	2,6	m ²
Weight per pack	ISO23997	17,42	19,9	kg
Total thickness	ISO24337	4	4	mm
Top Layer thickness	EN429	0,55	0,55	mm
Core	-	Sound reducing, robust and waterproof Floorify® Rigid Core		
Finish	-	Protected with stain resistant Floorify® Quiet Sense Technology		
Locking method	-	Traditional glueless click under license of Unilin.		
Warranty				
 Usage class	ISO10582	33		
 CE	EN 14041	DoP FF001		
Warranty	Residential / Commercial	Residential: 20 years (25 years when installed on Floorify® Performance underlay) Commercial: 5 years only when installed on Floorify® Performance underlay		
Technical data				
	Norm	Norm Requirements		Floorify values
 Wear resistance	EN13329, Annex E	≥ 2000 cycles		≥ 4000 cycles - AC4
 Impact resistance	EN13329	≥ 1600 mm		In combination with Floorify underlays: 1800mm - IC3
 Residual indentation	ISO24343-1	≤ 0,2 mm		In combination with Floorify underlays: no visible changes
 Stain resistance	EN423	Groups 1 and 2: grade 5; Group 3: grade 4		Groups 1, 2 and 3: grade 5;
 UV resistance	ISO 105-B02:1994, Method 3a	≥ 6		> 6
 Fire classification	EN 13501-1 ISO 9239-1			Bfl-s1
 Dimensional stability	EN ISO23999 6uur bij 80C	≤ 0,25 %		≤ 0,10 %
 Locking strength	ISO24334	Long side: ≥ 1kN/m	Short side: ≥ 1,5kN/m	Long side: > 4,5kN/m Short side: > 4,5kN/m

	Displacement of furniture feet	ISO 16581	Foot 0,1mm / 32kg	No changes
	Castor chairs	ISO 4918	≥ 25000 cycles: No delamination, no disturbance	In combination with Floorify underlays: no visible changes
	Slip resistance	EN13893 EN 16165	-	DS R10
	Swelling	ISO24336	< 18%	0%
	Thermal resistance (floor + underlay)	EN12667	< 0,15R (m²K/W)	0.0213 R24 (m²K/W) (0.0120 floor + 0.0093 Performance Underlay) 0.0660 R24 (m²K/W) (0.0120 floor + 0.0540 Comfort)
	Floor heating	Appropriate for all standard heating systems IN cement flooring. NOT appropriate or tested with heating films.		
	Impact sound improvement	ISO 10140 / ISO717-2	ΔLw18dB	In combination with Floorify® Comfort underlay: ΔLw20dB (ΔLin10dB)
Dangerous Substances				
	Formaldehyde emission	EN14041 / EN717-1	E1	
	TVOC 28 days	< 1000µg/m³	< 10µg/m³	
	Emissions in the interior air	Decree n° 2011-321	A+	
	REACH	-	Floorify® floors and accessories are fully REACH compliant	
	Plasticizers	-	DOPT - virgin PVC - 100% orthophtalate free	

Floorify NV reserves the right to make alterations to material and structures when this serves to improve the quality
Floorify NV, Kruisboommolenstraat 30A 8800 ROESELARE, BELGIUM - Email: sales@Floorify.com - T+32 (0)51 140 180